

BS1701**3 1/2 Digits Multimeter with Diode and Continuity**

Features:

- 3 1/2 Digits LCD display
- DC Voltage 200mV to 600V
- AC Voltage 200V/600V
- DC Current 200 μ A to 10A
- Resistance 200 Ω to 20M Ω
- Data Hold
- Conform to IEC1010/EN61010-1, CE-EMC & LVD CATIII 600V

**General Specifications**

Display	: 3 1/2 digits LCD with max. reading of 1999.
Polarity	: Automatic, (-) negative polarity indication.
Zero adjustment	: Automatic.
Over range indication	: Only the MSD "1" is displayed.
Power	: Single, standard 9 volt battery NEDA 1604, JIS 006P, IEC6F22.
Dimension	: 75 (W) x 144 (H) x 40 (D) mm.
Weight	: Approx. 180 g (including battery).

Electrical Specification

Accuracies are \pm (% of reading + number of least significant digits) at $23^{\circ}\text{C}\pm 5^{\circ}\text{C}$, less than 75%RH

DC Voltage Measurement

Range	Resolution	Accuracy	Input Impedance	Overload Protection
200mV	0.1mV	$\pm(0.8\% \text{ Read.} + 2\text{dgt})$	10M Ω	250V DC/AC rms
2V	0.001V			600V DC/AC rms
20V	0.01V			
200V	0.1V			
600V	1V			

AC Voltage Measurement

Range	Resolution	Accuracy	Input Impedance	Overload Protection
200V	0.1V	$\pm(1.5\% \text{ Read.} + 5\text{dgt})$	10M Ω	600V DC/AC rms
600V	1V			

Frequency range: 40-400Hz

DC Current Measurement

Range	Resolution	Accuracy	Voltage drop	Overload Protection
200 μA	0.1 μA	$\pm(1.0\% \text{ Read.} + 2\text{dgt})$	200mV	Fast 200mA/250V Fuse
2mA	0.001mA			
20mA	0.01mA			
200mA	0.1mA			
10A	0.01A	$\pm(1.5\% \text{ Read.} + 5\text{dgt})$		Unfused 10A 15sec.



Resistance Measurement

Range	Resolution	Accuracy	Open circuit voltage	Overload Protection
200Ω	0.1Ω	±(0.8% Read. + 2dgt)	<3.0V	250V DC/AC rms <30 sec
2kΩ	0.001kΩ			
20kΩ	0.01kΩ			
200kΩ	0.1kΩ			
2MΩ	0.001MΩ	±(1.2% Read. + 5dgt)		
20MΩ	0.01MΩ			

Diode Test

Range	Accuracy	Open circuit voltage	Overload Protection
▶+	Approx. 1mA	3.0V	250V DC/AC rms <30 sec

Continuity Test

Range	Buzzer sounds when resistance value < 100Ω	Open circuit voltage	Overload Protection
•))		3.0V	250V DC/AC rms <30 sec

CALTEK INDUSTRIAL (HONG KONG) LIMITED		www.bstcaltek.com
<u>Hong Kong Office</u>		
Address: Unit 11 10/F, Kwai Cheong Center, 50 Kwai Cheong Road, Kwai Chung, N.T., Hong Kong		
Email: caltek@caltek.com.hk	Tel: (852) 2401-1222	Fax: (852) 2420-3472
<u>Singapore Office</u>		
Level 15, Suite 27, Prudential Tower, 30 Cecil Street, Singapore 049712		
Email: caltek_sg@caltek.com.hk	Tel: (65) 6232-2903	Fax: (65) 6232-2888