

## BS-3 Voltage Checker



### Features:

- Voltage Range 6V/12V/24V/50V/120V/230V/400V
- LED light up to the voltage reading
- Frequency Range 0~60Hz
- Imitated double injection robust case
- High reliability and safety
- Extremely low cost, no serviceable part required
- Conforms to EN61010, CAT III 1000V CE-EMC & LVD

Packing: Complete with Instruction Manual, blister pack





**TECHNICAL SPECIFICATIONS**

Rated Voltage Range : 6V/12V/24V/50V/120V/230V/400V  
AC Voltage : 6V to 400V  
DC Voltage : 6V to 400V  
Accuracy : Indicator light up start at 85% of rated voltage  
Indicator Type : LED  
Frequency Response : 0 to 60Hz  
Maximum Test Time : 30 seconds, with 240 seconds pause interval  
Operating and Storage : 5°C to 40°C, 85% RH  
Condition  
Dimension : Main Probe: 205\*35\*35mm; Test Probe: 28\*28\*170mm;  
Connection cable length: 900mm  
Weight : Approximate 200g (excluding packaging)

**CALTEK INDUSTRIAL (HONG KONG) LIMITED** [www.bstcaltek.com](http://www.bstcaltek.com)

Hong Kong Office

Address: Unit 11 10/F, Kwai Cheong Center, 50 Kwai Cheong Road, Kwai Chung, N.T., Hong Kong  
Email: [caltek@caltek.com.hk](mailto:caltek@caltek.com.hk) Tel: (852) 2401-1222 Fax: (852) 2420-3472

Singapore Office

Level 15, Suite 27, Prudential Tower, 30 Cecil Street, Singapore 049712  
Email: [caltek\\_sg@caltek.com.hk](mailto:caltek_sg@caltek.com.hk) Tel: (65) 6232-2903 Fax: (65) 6232-2888