



## BS-3S Voltage Checker



### Features:

- Voltage Range 6V//50V/120V/230V/400V DC/AC
- LED/Neon lamp light up to the voltage reading
- Frequency Range 0~100Hz
- Imitated double injection robust case
- High reliability and safety
- Extremely low cost, no serviceable part or battery required
- Conforms to EN61010, CAT III 1000V CE-EMC & LVD

Packing: Complete with Instruction Manual, blister pack





**TECHNICAL SPECIFICATIONS**

Rated Voltage Range	: 6V/50V/120V/230V/400V
AC Voltage	: 6V to 400V
DC Voltage	: 6V to 400V
Test Current	: Maximum 5.2mA
Accuracy	: Indicator light up start at 85% of rated voltage
Indicator Type	: LED and Neon Lamp
Frequency Response	: 0 to 100Hz
Maximum Test Time	: 30 seconds, with 240 seconds pause interval
Operating and Storage Condition	: 5°C to 40°C, 85% RH
Dimension	: Main Probe: 205*35*35mm; Test Probe: 28*28*170mm; Connection cable length: 900mm
Weight	: Approximate 200g (excluding packaging)



**CALTEK INDUSTRIAL (HONG KONG) LIMITED**      [www.bstcaltek.com](http://www.bstcaltek.com)

Hong Kong Office

Address: Unit 11 10/F, Kwai Cheong Center, 50 Kwai Cheong Road, Kwai Chung, N.T., Hong Kong  
Email: [caltek@caltek.com.hk](mailto:caltek@caltek.com.hk)      Tel: (852) 2401-1222      Fax: (852) 2420-3472

Singapore Office

Level 15, Suite 27, Prudential Tower, 30 Cecil Street, Singapore 049712  
Email: [caltek\\_sg@caltek.com.hk](mailto:caltek_sg@caltek.com.hk)      Tel: (65) 6232-2903      Fax: (65) 6232-2888