

CM5091

3 1/2 Digits Multi Function Multimeter

Features:

- 3 1/2 Digits LCD display
- Max. reading 1999
- Auto power off
- DC voltage 200mV up to 600V
- AC voltage 200mV up to 600V
- DC current 200 μ A up to 10A (fused)
- Resistance 200 Ω up to 20M Ω
- Diode test
- Continuity test
- Data hold
- Low battery warning display
- All ranges 600volt overload protection
- Wrong terminal inserting warning beeper
- German technology double moulded casing
- Power single 9V NEDA 1604
- Conform to IEC1010/EN61010
CAT III 600V, CE-EMC & LVD



General Specifications

Display	: 3 1/2 digits LCD with max. reading of 1999.
Polarity	: Automatic, (-) negative polarity indication.
Zero adjustment	: Automatic.
Over range indication	: Only the MSD "1" is displayed.
Power	: Single, standard 9 volt battery NEDA 1604, JIS 006P, IEC6F22.
Dimension	: 93 (W) x 194 (H) x 39.4 (D) mm.
Weight	: Approx. 400 g (including battery).

Due to our policy of continual product development we reserve the right to amend the specifications of all mentioned products without notice.



Electrical Specification

Accuracies are \pm (% of reading + number of least significant digits) at 23°C \pm 5°C, less than 75%RH

DC voltage measurement

Range	Resolution	Accuracy	Input impedance	Overload Protection
200mV	0.1mV	$\pm(0.8\% \text{Read.} + 1 \text{dgt})$	10M Ω	600Vrms
2V	0.001V			
20V	0.01V			
200V	0.1V			
600V	1V			

AC voltage measurement

Range	Resolution	Accuracy	Input impedance	Overload Protection
200mV	0.1mV	$\pm(1.5\% \text{Read.} + 10 \text{dgt})$	10M Ω	600Vrms
2V	0.001V			
20V	0.01V			
200V	0.1V			
600V	1V			

Frequency Range: 40 – 400Hz

DC current measurement

Range	Resolution	Accuracy	Voltage drop	Overload Protection
200 μ A	0.1 μ A	$\pm(1.0\% \text{Read.} + 2 \text{dgt})$	200mV	Fuse 2A/600V Rapid
2mA	0.001mA			
20mA	0.01mA			
200mA	0.1mA	$\pm(1.2\% \text{Read.} + 2 \text{dgt})$		
2A	1mA	$\pm(2.0\% \text{Read.} + 5 \text{dgt})$		Fuse 10A/600V
10A	0.01A			Rapid

Due to our policy of continual product development we reserve the right to amend the specifications of all mentioned products without notice.



Resistance measurement

Range	Resolution	Accuracy	Max open circuit voltage	Overload Protection
200Ω	0.1Ω	±(1.0%Read. + 3dgt)	≤ 700mV	600Vrms
2kΩ	0.001kΩ			
20kΩ	0.01kΩ			
200kΩ	0.1kΩ			
2MΩ	0.001MΩ	±(1.2%Read. + 5dgt)		
20MΩ	0.01MΩ	±(1.5%Read. + 3dgt)		

Diode Test

Range	Accuracy	Test current	Max open circuit voltage	Overload Protection
2000mV	±(2%Read. + 2dgt)	Approx. 1mA	3.0V	600Vrms

Continuity Test

Range	Accuracy	Test current	Max open circuit voltage	Overload Protection
2000Ω(*)	±(2%Read. + 2dgt)	Approx. 1mA	3.0V	600Vrms

(*) The instrument emits a sound signal when the resistance value is lower than 100Ω.

CALTEK INDUSTRIAL (HONG KONG) LIMITED

www.caltek.com.hk

Hong Kong Office

Address: Flat E, 12/F, Effort Industrial Building, 2-8 Kung Yip Street, Kwai Chung, N.T., Hong Kong

Email: caltek@caltek.com.hk

Tel: (852) 2401-1222

Fax: (852) 2420-3472

Singapore Office

Level 15, Suite 27, Prudential Tower, 30 Cecil Street, Singapore 049712

Email: caltek_sg@caltek.com.hk

Tel: (65) 6232-2903

Fax: (65) 6232-2888

Due to our policy of continual product development we reserve the right to amend the specifications of all mentioned products without notice.